




DESCRIPTION

Three complete series of Zener diodes are offered in the convenient, surface mount plastic SOD-123 package.

These devices provide a convenient alternative to the leadless 34-package style.

The MSZ5221B~MSZ5272B are available in SOD-123 Package.

PIN DESCRIPTION



FEATURES

- 500mW Rating on FR-4 or FR-5 Board
- Wide Zener Reverse Voltage Range: 2.4V to 110V
- Package Designed for Optimal Automated Board Assembly
- Small Package Size for High Density Applications
- General Purpose, Medium Current
- ESD Rating of Class3 (>16kV) per Human Body Model
- Available in SOD-123 Package

MECHANICAL CHARACTERISTICS

Case: Void-free, transfer-molded, thermosetting plastic case

Finish: Corrosion resistant finish, easily solderable

Maximum Case Temperature For Soldering

Purposes: 260°C for 10 Seconds

Polarity: Cathode indicated by polarity band

Flammability Rating: UL 94 V-0



ORDERING INFORMATION

Package Type	Part Number
SOD-123	MSZ5221B
	MSZ5222B
	MSZ5223B
	MSZ5224B
	MSZ5225B
	MSZ5226B
	MSZ5227B
	MSZ5228B
	MSZ5229B
	MSZ5230B
	MSZ5231B
	MSZ5232B
	MSZ5233B
	MSZ5234B
	MSZ5235B
	MSZ5236B
	MSZ5237B
	MSZ5238B
	MSZ5239B
	MSZ5240B
	MSZ5241B
	MSZ5242B
	MSZ5243B
	MSZ5244B
	MSZ5245B

Package Type	Part Number
SOD-123	MSZ5246B
	MSZ5247B
	MSZ5248B
	MSZ5250B
	MSZ5251B
	MSZ5252B
	MSZ5253B
	MSZ5254B
	MSZ5255B
	MSZ5256B
	MSZ5257B
	MSZ5258B
	MSZ5259B
	MSZ5260B
	MSZ5261B
	MSZ5262B
	MSZ5263B
	MSZ5264B
	MSZ5265B
	MSZ5266B
MSZ5267B	
MSZ5268B	
MSZ5269B	
MSZ5270B	
MSZ5272B	
Note	3,000pcs /Reel
AiT provides all RoHS Compliant Products	



ABSOLUTE MAXIMUM RATINGS

P_D , Total Power Dissipation on FR-5 Board, ^{NOTE1}	
@ $T_L = 75^\circ\text{C}$	500mW
Derated above 75°C	6.7mW/ $^\circ\text{C}$
$R_{\theta JA}$, Thermal Resistance, Junction-to-Ambient ^{NOTE 2}	340 $^\circ\text{C}/\text{W}$
$R_{\theta JL}$, Thermal Resistance, Junction-to-Lead ^{NOTE 2}	150 $^\circ\text{C}/\text{W}$
T_J, T_{STG} , Junction and Storage Temperature Range	-55 $^\circ\text{C}$ to +125 $^\circ\text{C}$


Stresses above may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated in the Electrical Characteristics are not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

NOTE1: FR-5 = 3.5 x 1.5 inches, using the minimum recommended footprint.

NOTE2: Thermal Resistance measurement obtained via infrared Scan Method.



ELECTRICAL PARAMETER



Zener Voltage Regulator

$T_A = 25^\circ\text{C}$ unless otherwise noted, $V_F = 0.95\text{V Max. @}I_F = 10\text{mA}$

Symbol	Parameter
V_Z	Reverse Zener Voltage @ I_{ZT}
I_{ZT}	Reverse Current
Z_{ZT}	Maximum Zener Impedance @ I_{ZT}
I_{ZK}	Reverse Current
Z_R	Maximum Zener Impedance @ I_{ZK}
I_R	Reverse Leakage Current @ V_R
V_R	Reverse Voltage
I_F	Forward Current
V_F	Forward Voltage @ I_F



ELECTRICAL CHARACTERISTICS

T_A = 25°C unless otherwise noted, V_F = 0.9V Max. @I_F = 10mA

Part Number	Zener Voltage ^{NOTE3+NOTE4}				Zener Impedance ^{NOTE5}			Leakage Current	
	V _Z (Volts)			@I _{ZT}	Z _{ZT} @I _{ZT}	Z _{ZK} @I _{ZK}		I _R @V _R	
	Min	Nom	Max	mA	Ω	Ω	mA	μA	Volts
MSZ5221B	2.28	2.4	2.52	20	30	1200	0.25	100	1
MSZ5222B	2.38	2.5	2.63	20	30	1250	0.25	100	1
MSZ5223B	2.57	2.7	2.84	20	30	1300	0.25	75	1
MSZ5224B	2.66	2.8	2.94	20	30	1400	0.25	75	1
MSZ5225B	2.85	3.0	3.15	20	29	1600	0.25	50	1
MSZ5226B	3.14	3.3	3.47	20	28	1600	0.25	25	1
MSZ5227B	3.42	3.6	3.78	20	24	1700	0.25	15	1
MSZ5228B	3.71	3.9	4.10	20	23	1900	0.25	10	1
MSZ5229B	4.09	4.3	4.52	20	22	2000	0.25	5	1
MSZ5230B	4.47	4.7	4.94	20	19	1900	0.25	5	2
MSZ5231B	4.85	5.1	5.36	20	17	1600	0.25	5	2
MSZ5232B	5.32	5.6	5.88	20	11	1600	0.25	5	3
MSZ5233B	5.70	6.0	6.30	20	7	1600	0.25	5	3.5
MSZ5234B	5.89	6.2	6.51	20	7	1000	0.25	5	4
MSZ5235B	6.46	6.8	7.14	20	5	750	0.25	3	5
MSZ5236B	7.13	7.5	7.88	20	6	500	0.25	3	6
MSZ5237B	7.79	8.2	8.61	20	8	500	0.25	3	6.5
MSZ5238B	8.27	8.7	9.14	20	8	600	0.25	3	6.5
MSZ5239B	8.65	9.1	9.56	20	10	600	0.25	3	7
MSZ5240B	9.50	10	10.50	20	17	600	0.25	3	8
MSZ5241B	10.45	11	11.55	20	22	600	0.25	2	8.4
MSZ5242B	11.40	12	12.60	20	30	600	0.25	1	9.1
MSZ5243B	12.35	13	13.65	9.5	13	600	0.25	0.5	9.9
MSZ5244B	13.30	14	14.70	9.0	15	600	0.25	0.1	10
MSZ5245B	14.25	15	15.75	8.5	16	600	0.25	0.1	11
MSZ5246B	15.20	16	16.80	7.8	17	600	0.25	0.1	12
MSZ5247B	16.15	17	17.85	7.4	19	600	0.25	0.1	13
MSZ5248B	17.10	18	18.90	7.0	21	600	0.25	0.1	14
MSZ5250B	19.00	20	21.00	6.2	25	600	0.25	0.1	15
MSZ5251B	20.90	22	23.10	5.6	29	600	0.25	0.1	17
MSZ5252B	22.80	24	25.20	5.2	33	600	0.25	0.1	18
MSZ5253B	23.75	25	26.25	5.0	35	600	0.25	0.1	19
MSZ5254B	25.65	27	28.35	4.6	41	600	0.25	0.1	21
MSZ5255B	26.60	28	29.40	4.5	44	600	0.25	0.1	21



T_A = 25°C unless otherwise noted, V_F = 0.9V Max. @I_F = 10mA

Part Number	Zener Voltage ^{NOTE3+NOTE4}				Zener Impedance ^{NOTE5}			Leakage Current	
	V _Z (Volts)			@I _{ZT}	Z _{ZT} @I _{ZT}	Z _{ZK} @I _{ZK}		I _R @V _R	
	Min	Nom	Max	mA	Ω	Ω	mA	μA	Volts
MSZ5256B	28.50	30	31.50	4.2	49	600	0.25	0.1	23
MSZ5257B	31.35	33	34.65	3.8	58	700	0.25	0.1	25
MSZ5258B	34.20	36	37.80	3.4	70	700	0.25	0.1	27
MSZ5259B	37.05	39	40.95	3.2	80	800	0.25	0.1	30
MSZ5260B	40.85	43	45.15	3.0	93	900	0.25	0.1	33
MSZ5261B	44.65	47	49.35	2.7	105	1000	0.25	0.1	36
MSZ5262B	48.45	51	53.55	2.5	125	1100	0.25	0.1	39
MSZ5263B	53.20	56	58.80	2.2	150	1300	0.25	0.1	43
MSZ5264B	57.00	60	63.00	2.1	170	1400	0.25	0.1	46
MSZ5265B	58.90	62	65.10	2.0	185	1400	0.25	0.1	47
MSZ5266B	64.60	68	71.40	1.8	230	1600	0.25	0.1	52
MSZ5267B	71.25	75	78.75	1.7	270	1700	0.25	0.1	56
MSZ5268B	77.90	82	86.10	1.5	330	2000	0.25	0.1	62
MSZ5269B	82.65	87	91.35	1.4	370	2200	0.25	0.1	68
MSZ5270B	86.45	91	95.55	1.4	400	2300	0.25	0.1	69
MSZ5272B	104.5	110	115.5	1.1	750	3000	0.25	0.1	84

NOTE3: The type numbers shown have a standard tolerance of ±5% on the nominal Zener voltage.

NOTE4: Nominal Zener voltage is measured with the device junction in thermal equilibrium at T_L = 30°C ± 1°C.

NOTE5: Z_{ZT} and Z_{ZK} are measured by dividing the AC voltage drop across the device by the ac current applied.

The specified limits are for I_{Z(AC)} = 0.1 I_{Z(dc)} with the AC frequency = 1KHz.



TYPICAL CHARACTERISTICS

Figure 1. Temperature Coefficients
(Temperature Range -55°C to +150°C)




Figure 2. Temperature Coefficients
(Temperature Range -55°C to +150°C)




Figure 3. Steady State Power Derating




Figure 4. Maximum Nonrepetitive Surge Power




Figure 5. Effect of Zener Voltage on Zener Impedance




Figure 6. Typical Forward Voltage






Figure 7. Typical Capacitance




Figure 8. Typical Leakage Current




Figure 9. Zener Voltage versus Zener Current
(V_Z Up to 12 V)






Figure 10. Zener Voltage versus Zener Current
(12 V to 91 V)





PACKAGE INFORMATION

Dimension in SOD-123 Package (Unit: mm)



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.055	0.071	1.40	1.80
B	0.100	0.112	2.55	2.85
C	0.037	0.053	0.95	1.35
D	0.020	0.028	0.50	0.70
E	0.004	-	0.25	-
H	0.000	0.004	0.00	0.10
J	-	0.006	-	0.15
K	0.140	0.152	3.55	3.85



IMPORTANT NOTICE

AiT Components (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Components' integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or severe property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Components assumes no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.