



DESCRIPTION

The MBT2907AD is available in SC-88 Package.


FEATURES

- RoHS compliance
- Available in SC-88 Package

ORDERING INFORMATION

| Package Type | Part Number |
|--|----------------------|
| SC-88 | MBT2907AD |
| Note | SPQ: 3,000pcs / Reel |
| AiT provides all RoHS Compliant Products | |

PIN DESCRIPTION



PIN

1. EMITTER 2
2. BASE 2
3. COLLECTOR 1
4. EMITTER 1
5. BASE 1
6. COLLECTOR 2



ABSOLUTE MAXIMUM RATINGS

| | |
|---|----------------------|
| V _{CEO} , Collector-Emitter Voltage | -60Vdc |
| V _{CBO} , Collector-Base Voltage | -60Vdc |
| V _{EBO} , Emitter-Base Voltage | -5.0Vdc |
| I _C , Collector Current-Continuous | -600mA _{dc} |

Stresses above may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated in the Electrical Characteristics are not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

THERMAL CHARACTERISTICS

| Parameter | Symbol | Max | Unit |
|---|-----------------------------------|-------------|-------------|
| Total Device Dissipation FR-5 Board ^{NOTE1} T _A = 25°C Derate above 25°C | P _D | 225 1.8 | mW mW/°C |
| Thermal Resistance, Junction to Ambient | R _{θJA} | 556 | °C/W |
| Total Device Dissipation Alumina Substrate ^{NOTE2} T _A = 25°C Derate above 25°C | P _D | 300 2.4 | mW mW/°C |
| Thermal Resistance, Junction to Ambient | R _{θJA} | 417 | °C/W |
| Junction and Storage Temperature | T _J , T _{STG} | -55 to +150 | °C |

NOTE1: FR-5 = 1.0 x 0.75 x 0.062 in.

NOTE2: Alumina = 0.4 x 0.3 x 0.024 in. 99.5% alumina.



ELECTRICAL CHARACTERISTICS

T_A=25°C, unless otherwise noted

| Parameter | Symbol | Conditions | Min. | Max. | Unit |
|---|----------------------|---|------|--------|------------------|
| OFF CHARACTERISTICS | | | | | |
| Collector-Emitter Breakdown Voltage ^{NOTE3} | V _{(BR)CEO} | I _C = -10mA _{dc} , I _B = 0 | -60 | - | V _{dc} |
| Collector-Emitter Breakdown Voltage | V _{(BR)CBO} | I _C = -10μA _{dc} , I _E = 0 | -60 | - | V _{dc} |
| Emitter-Base Breakdown Voltage | V _{(BR)EBO} | I _E = -10μA _{dc} , I _C = 0 | -5.0 | - | V _{dc} |
| Collector Cutoff Current | I _{CEX} | V _{CB} = -30V _{dc} , I _{BE(OFF)} = -0.5V _{dc} | - | -50 | nA _{dc} |
| Collector Cutoff Current | I _{CBO} | V _{CB} = -50V _{dc} , I _E = 0 | - | -0.010 | μA _{dc} |
| | | V _{CB} = -50V _{dc} , I _E = 0, T _A = 125°C | - | -10 | |
| Base Current | I _B | V _{CE} = -30V _{dc} , V _{EB(off)} = -0.5V _{dc} | - | -50 | nA _{dc} |
| ON CHARACTERISTICS | | | | | |
| DC Current Gain | h _{FE} | I _C = -0.1mA _{dc} , V _{CE} = -10V _{dc} | 75 | - | |
| | | I _C = -1.0mA _{dc} , V _{CE} = -10V _{dc} | 100 | - | |
| | | I _C = -10mA _{dc} , V _{CE} = -10V _{dc} | 100 | - | |
| | | I _C = -150mA _{dc} , V _{CE} = -10V _{dc} ^{NOTE3} | 100 | 300 | |
| | | I _C = -500mA _{dc} , V _{CE} = -10V _{dc} ^{NOTE3} | 50 | - | |
| Collector-Emitter Saturation Voltage ^{NOTE3} | V _{CE(sat)} | I _C = -150mA _{dc} , I _B = -15mA _{dc} | - | -0.4 | V _{dc} |
| | | I _C = -500mA _{dc} , I _B = -50mA _{dc} | - | -1.6 | |
| Base-Emitter Saturation Voltage ^{NOTE3} | V _{BE(sat)} | I _C = -150mA _{dc} , I _B = -15mA _{dc} | - | -1.3 | V _{dc} |
| | | I _C = -500mA _{dc} , I _B = -50mA _{dc} | - | -2.6 | |
| SMALL-SIGNAL CHARACTERISTICS | | | | | |
| Current-Gain-Bandwidth Product ^{NOTE3,4} | f _T | I _C = -50mA _{dc} , V _{CE} = -20V _{dc} , f = 100MHz | 200 | - | MHz |
| Output Capacitance | C _{obo} | V _{CB} = -10V _{dc} , I _E = 0, f = 1.0MHz | - | 8.0 | pF |
| Input Capacitance | C _{ibo} | V _{EB} = -2.0V _{dc} , I _C = 0, f = 1.0MHz | - | 30 | pF |
| SWITCHING CHARACTERISTICS | | | | | |
| Turn-On Time | t _{on} | V _{CC} = -30V _{dc} , I _C = -150mA _{dc} , I _{B1} = -15mA _{dc} | - | 45 | ns |
| Delay Time | t _d | | - | 10 | |
| Rise Time | t _r | | - | 40 | |
| Fall Time | t _f | V _{CC} = -6.0V _{dc} , I _C = -150mA _{dc} , I _{B1} = I _{B2} = 15mA _{dc} | - | 60 | ns |
| Storage Time | t _s | | - | 225 | |
| Turn-Off Time | t _{off} | | - | 280 | |

NOTE3: Pulse Test: Pulse Width < 300μs, Duty Cycle < 2.0%.

NOTE4: f_T is defined as the frequency at which |h_{fe}| extrapolates to unity.



TYPICAL CHARACTERISTICS

Figure 1. Delay and Rise Time Test Circuit




Figure 2. Storage and Fall Time Test Circuit




Figure 3. DC Current Gain




Figure 4. Collector Saturation Region






Figure 5. Turn-On Time





Figure 6. Turn-Off Time



TYPICAL SMALL-SIGNAL CHARACTERISTICS NOISE FIGURE ($V_{CE} = 10V_{dc}$, $T_A = 25^\circ C$)

Figure 7. Frequency Effects




Figure 8. Source Resistance Effects




Figure 9. Capacitances




Figure 10. Current-Gain-Bandwidth Product






Figure 11. Collector Emitter Saturation Voltage vs. Collector Current




Figure 12. Base Emitter Saturation Voltage vs. Collector Current




Figure 13. Base Emitter Voltage vs. Collector Current




Figure 14. Temperature Coefficients






Figure 15. Safe Operating Area





PACKAGE INFORMATION

Dimension in SC-88 Package (Unit: mm)



| DIM | INCHES | | MILLIMETERS | |
|-----|-----------|-------|-------------|------|
| | MIN | MAX | MIN | MAX |
| A | 0.071 | 0.087 | 1.80 | 2.20 |
| B | 0.045 | 0.053 | 1.15 | 1.35 |
| C | 0.031 | 0.043 | 0.80 | 1.10 |
| D | 0.004 | 0.012 | 0.10 | 0.30 |
| G | 0.026 BSC | | 0.65 BSC | |
| H | - | 0.004 | - | 0.10 |
| J | 0.004 | 0.010 | 0.10 | 0.25 |
| K | 0.004 | 0.012 | 0.10 | 0.30 |
| N | 0.008 REF | | 0.20 REF | |
| S | 0.079 | 0.087 | 2.00 | 2.20 |



IMPORTANT NOTICE

AiT Components (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Components' integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or severe property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Components assumes no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.