



## DESCRIPTION

The SM220BF~SM2200BF are available in SMB Package.

## ORDERING INFORMATION

Package Type	Part Number
SMBF	SM220BF
	SM240BF
	SM260BF
	SM280BF
	SM2100BF
	SM2120BF
	SM2150BF
	SM2200BF
Note	SPQ: 5,000pcs/Reel
AiT provides all RoHS Compliant Products	

## FEATURES

- Metal silicon junction, majority carrier conduction
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- Available in SMBF Package

## MECHANICAL DATA

Case: SMBF

Terminals: Solderable per MIL-STD-750,  
Method 2026

Approx. Weight: 57mg / 0.002oz

## PIN DESCRIPTION





**ABSOLUTE MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %

Parameter Symbol	Symbol	SM 220BF	SM 240BF	SM 260BF	SM 280BF	SM 2100BF	SM 2120BF	SM 2150BF	SM 2200BF	Unit
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	20	40	60	80	100	120	150	200	V
Maximum RMS Voltage	$V_{RMS}$	14	28	42	56	70	84	105	140	V
Maximum DC Blocking Voltage	$V_{DC}$	20	40	60	80	100	120	150	200	V
Maximum Average Forward Rectified Current at	$I_{F(AV)}$	2.0								A
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed On Rated Load (JEDEC Method)	$I_{FSM}$	55				45				A
Max Instantaneous Forward Voltage at 2A	$V_F$	0.55		0.70		0.85		0.95		V
Maximum DC Reverse Current at Rated DC Blocking Voltage	$I_R$	0.5 5		0.3 3						mA
Typical Junction Capacitance <sup>NOTE1</sup>	$C_J$	250			110				pF	
Typical Thermal Capacitance <sup>NOTE2</sup>	$R_{\theta JA}$	65								°C/W
Operating Temperature Range	$T_J$	-55 to +125								°C
Storage Temperature Range	$T_{STG}$	-55 to +150								°C

NOTE1: Measured at 1MHz and applied reverse voltage of 4 V D.C.

NOTE2: P.C.B. mounted with 0.5" x 0.5" (12.7 x 12.7 mm) copper pad areas.



**TYPICAL PERFORMANCE CHARACTERISTICS**

T<sub>A</sub> = 25°C unless otherwise noted.

Figure. 1 Forward Current Derating Curve




Figure. 2 Typical Reverse Characteristics




Figure. 3 Typical Forward Characteristic




Figure. 4 Typical Junction Capacitance




Figure. 5 Maximum Non-Repetitive Peak Forward Surge Current





Figure. 6 Typical Transient Thermal Impedance







**PACKAGE INFORMATION**

Dimension in SMBF Package (Unit: mm)

Plastic surface mounted package; 2 leads



The recommended mounting pad size



Unit: mm(mil)

UNIT		A	C	D	E	HE	e	g	∠
mm	Max	1.3	0.26	4.4	3.7	5.5	2.2	1.0	9°
	Min	1.1	0.18	4.2	3.5	5.1	1.9		
mil	Max	51	10	173	146	216	86	40	
	Min	43	7	165	138	200	75		



## IMPORTANT NOTICE

AiT Components (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Components' integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or severe property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Components assumes no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.