



DESCRIPTION

The SM520A~SM5200A are available in SMA Package.

ORDERING INFORMATION

Package Type	Part Number
SMA	SM520A
	SM540A
	SM560A
	SM580A
	SM5100A
	SM5120A
	SM5150A
	SM5200A
Note	5,000pcs/Reel
AiT provides all RoHS Compliant Products	

FEATURES

- Metal silicon junction, majority carrier conduction
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- Available in SMA Package

MECHANICAL DATA

Case: SMA

Terminals: Solderable per MIL-STD-750,
Method 2026

Approx. Weight: 60mg / 0.0021oz

PIN DESCRIPTION





ABSOLUTE MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %

Parameter	Symbol	SM 520A	SM 540A	SM 560A	SM 580A	SM 5100A	SM 5120A	SM 5150A	SM 5200A	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	20	40	60	80	100	120	150	200	V
Maximum RMS Voltage	V_{RMS}	14	28	42	56	70	84	105	140	V
Maximum DC Blocking Voltage	V_{DC}	20	40	60	80	100	120	150	200	V
Maximum Average Forward Rectified Current	$I_{F(AV)}$	5.0								A
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	120				100				A
Max Instantaneous Forward Voltage at 5A	V_F	0.55	0.70		0.85				V	
Maximum DC Reverse Current at Rated DC Reverse Voltage	I_R	$T_A=25^{\circ}C$	1.0						mA	
		$T_A=100^{\circ}C$	50							
Typical Junction Capacitance ^{NOTE1}	C_J	500	300						pF	
Typical thermal Resistance ^{NOTE2}	$R_{\theta JA}$	60								°C/W
Operating Junction Temperature Range	T_J	-55 to +150								°C
Storage Temperature Range	T_{stg}	-55 to +150								°C

NOTE1: Measured at 1MHz and applied reverse voltage of 4 V D.C.

NOTE2: P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.



TYPICAL PERFORMANCE CHARACTERISTICS

Figure. 1 Forward Current Derating Curve




Figure. 2 Typical Reverse Characteristics




Figure. 3 Typical Forward Characteristic




Figure. 4 Typical Junction Capacitance




Figure. 5 Maximum Non-Repetitive Peak Forward Surge Current





Figure. 6 Typical Transient Thermal Impedance







PACKAGE INFORMATION

Dimension in SMA Package (Unit: mm)

Plastic surface mounted package; 2 leads



The recommended mounting pad size



Unit : $\frac{\text{mm}}{\text{mil}}$

UNIT		A	D	E	H _E	c	e	g
mm	max	2.2	4.83	2.9	5.4	0.31	1.7	1.5
	min	1.9	4.32	2.3	4.7	0.12	1.2	0.9
mil	max	87	190	114	213	12	67	59
	min	75	170	91	185	5	47	35



IMPORTANT NOTICE

AiT Components (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Components' integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or severe property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Components assumes no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.