



DESCRIPTION

The SODZ5.1A-SH~SODZ200A-SH are available in SOD-123FL Package

ORDERING INFORMATION

Package Type	Part Number	
SOD-123FL	SODZ5.1A-SH	SODZ36A-SH
	SODZ5.6A-SH	SODZ39A-SH
	SODZ6.2A-SH	SODZ43A-SH
	SODZ6.8A-SH	SODZ47A-SH
	SODZ7.5A-SH	SODZ51A-SH
	SODZ8.2A-SH	SODZ56A-SH
	SODZ9.1A-SH	SODZ62A-SH
	SODZ10A-SH	SODZ68A-SH
	SODZ11A-SH	SODZ75A-SH
	SODZ12A-SH	SODZ82A-SH
	SODZ13A-SH	SODZ91A-SH
	SODZ15A-SH	SODZ100A-SH
	SODZ16A-SH	SODZ110A-SH
	SODZ18A-SH	SODZ120A-SH
	SODZ20A-SH	SODZ130A-SH
	SODZ22A-SH	SODZ150A-SH
	SODZ24A-SH	SODZ160A-SH
	SODZ27A-SH	SODZ180A-SH
	SODZ30A-SH	SODZ200A-SH
	SODZ33A-SH	
Note	SPQ: 3,000pcs/Reel	
AiT provides all RoHS Compliant Products		

FEATURES

- 1 W SOD-123FL
- Zener voltage regulator diodes
- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Guarding for over voltage protection
- High temperature soldering guaranteed: 260°C/10 seconds at terminals
- Available in SOD-123FL Package

MECHANICAL DATA

Case: JEDEC SOD-123FL/MINI

SMA molded plastic

Terminals: Plated terminals, solderable per

MIL-STD-750, Method 2026

Polarity: Color band denoted cathode except Bipolar

Mounting Position: Any

Weight : Approximated 0.0155 gram

PIN DESCRIPTION





ELECTRICAL CHARACTERISTIC

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Parameter	Symbol	VALUE	Unit
Steady State Power Dissipation at $T_L=75^{\circ}\text{C}$ ^{NOTE1}	$P_{M(AV)}$	1.0	Watts
Z-current	I_Z	P_V/V_Z	mA
Peak Forward Surge Current, 8.3ms Single Half Sine-Wave Superimposed on Rated Load(JECED Method) ^{NOTE2}	I_{FSM}	40	Amps
Operating and Storage Temperature Range	T_J, T_{STG}	-50 to +150	°C

NOTE1: 8.0mm² (.013mm thick) land areas

NOTE2: 8.3ms single half sine-wave, duty cycle= 4 pulses per minutes maximum.



PRODUCT CHARACTERISTIC

Vz tolerance : ±5%; Tested with pulse tp=40ms; Ta=25°C Vfmax =1.2V @ If = 200mA P=1 W

Type	Zener	Current	A and B Suffix only			Leakage Current		Surge current	Maximum Regulator Current2)	
	Voltage	IzT	ZzT@IzT	Zzk@Izk	Zzk@Izk	IR	VR	IR @ Tamb=25°C	IzM @ Tamb =50°C	
	Vz@Lz									
	Volts	mA	Ohms	Ohms	mA	uA Max	Volts	mA	mA	
SODZ5.1A-SH	5.1	49	7	550	1	100	1.0	890	178	
SODZ5.6A-SH	5.6	45	5	600			2.0	810	164	
SODZ6.2A-SH	6.2	41	2	700			3.0	730	146	
SODZ6.8A-SH	6.8	37	4	1300			4	660	133	
SODZ7.5A-SH	7.5	34	4.5	1300			0.5	5	605	121
SODZ8.2A-SH	8.2	31	5.5	1300			0.5	6	550	110
SODZ9.1A-SH	9.1	28	6	1300			0.5	7	500	100
SODZ10A-SH	10	25	7	1300	0.25	20	7.6	454	91	
SODZ11A-SH	11	23	8	1300			8.4	414	83	
SODZ12A-SH	12	21	9	1300			9.1	380	76	
SODZ13A-SH	13	19	10	1300			9.9	344	69	
SODZ15A-SH	15	17	14	1300			11.4	304	61	
SODZ16A-SH	16	15.5	16	1300			12.2	285	57	
SODZ18A-SH	18	14	20	1300			13.7	250	50	
SODZ20A-SH	20	12.5	22	1300			15.2	225	45	
SODZ22A-SH	22	11.5	23	1300			16.7	205	41	
SODZ24A-SH	24	10.5	25	1300			18.2	190	38	
SODZ27A-SH	27	9.5	35	1300			20.6	170	34	
SODZ30A-SH	30	8.5	40	1500			22.8	150	30	
SODZ33A-SH	33	7.5	45	1500			25.1	135	27	
SODZ36A-SH	36	7	50	1500			27.4	125	25	
SODZ39A-SH	39	6.5	60	1500			29.7	115	23	
SODZ43A-SH	43	6	70	2500			32.7	110	22	
SODZ47A-SH	47	5.5	80	2500			35.8	95	19	
SODZ51A-SH	51	5	95	2500			38.8	90	18	
SODZ56A-SH	56	4.5	110	2500			42.6	80	16	
SODZ62A-SH	62	4	125	2500			47.1	70	14	
SODZ68A-SH	68	3.7	150	2500	51.7	65	13			
SODZ75A-SH	75	3.3	175	2500	56	60	12			
SODZ82A-SH	82	3	200	3000	62.2	55	11			
SODZ91A-SH	91	2.8	250	3000	69.2	50	10			
SODZ100A-SH	100	2.5	350	3000	76	45	9			
SODZ110A-SH	110	2	550	5000	83	42	8			
SODZ120A-SH	120	1.5	750	5500	90	38	7			
SODZ130A-SH	130	1	900	6000	98	34	6			
SODZ150A-SH	150	1	1200	6500	113	30	6			
SODZ160A-SH	160	1	1350	7000	120	28	6			
SODZ180A-SH	180	1	1650	8500	135	25	5			
SODZ200A-SH	200	1	1950	10000	150	23	4			



TYPICAL CHARACTERISTICS

Figure. 1 Vz--Iz




Figure. 2 Vz--Iz






Figure. 3 P--Ta






PACKAGE INFORMATION

Dimension in SOD-123FL (Unit: mm)



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	3.5	3.9	0.138	0.159
B	0.75	0.95	0.029	0.037
C	2.6	3.0	0.103	0.119
D	1.6	2.0	0.063	0.079
E	0.45 TYP		0.018 TYP	
H	0.9	1.2	0.036	0.047
J	0.12	0.22	0.005	0.009
K	0.8 TYP		0.032 TYP	

Suggested solder pad layout



Dimensions in inches and (millimeters)

PACKAGE	A	B	C
SOD-123FL	0.044(1.10)	0.040(1.00)	0.079(2.00)



IMPORTANT NOTICE

AiT Components (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Components' integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or servers property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Components assumes to no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.